

CLV622-1120

CLV62x

BAR CODE SCANNERS





Ordering information

Туре	Part no.
CLV622-1120	1041795

Other models and accessories → www.sick.com/CLV62x



Detailed technical data

Features

Version	Short Range
Connection type	Ethernet
Reading field	Front
Scanner design	Raster scanner
Focus	Fixed focus
Light source	Visible red light (655 nm)
Laser class	2 (IEC 60825-1:2014, EN 60825-1:2014)
Aperture angle	≤ 50°
Scanning frequency	400 Hz 1,200 Hz
Code resolution	0.15 mm 0.5 mm
Reading distance	55 mm 200 mm ¹⁾
Raster height, number of lines, at distance	15 mm, 8, 200 mm

 $^{^{1)}}$ For details see reading field diagram.

Mechanics/electronics

Electrical connection	2xM12 cylindrical connectors (12-pin male connector, 4-pin female connector) on swivel connector
Supply voltage	10 V DC 30 V DC
Power consumption	4.5 W
Housing	Aluminum die cast
Housing color	Light blue (RAL 5012)
Front screen	Glass
Enclosure rating	IP65 (DIN 40 050)
Protection class	III (VDE 0106/IEC 1010-1)
Weight	205 g, without connecting cable

 $^{^{1)}}$ Swivel connector is 15 mm longer.

Dimensions (L x W x H)	61 mm x 66 mm x 38 mm ¹⁾
MTBF	40,000 h

 $^{^{1)}}$ Swivel connector is 15 mm longer.

Performance

Readable code structures	1D
Bar code types	All current code types, Code 39, Code 128, Code 93, Codabar, GS1-128 / EAN 128, UPC / GTIN / EAN, Interleaved 2 of 5, Pharmacode, GS1 DataBar, Telepen, MSI/Plessey
Print ratio	2:1 3:1
No. of codes per scan	1 20 (Standard decoder) 1 6 (SMART620)
No. of codes per reading interval	1 50 (auto-discriminating)
No. of characters per reading interval	1,500 500 (for multiplexer function in CAN operation)
No. of multiple readings	199

Interfaces

interraces		
Ethernet		√ , TCP/IP
	Function	Host, AUX
	Data transmission rate	10/100 MBit/s
PROFINET		√
	Function	PROFINET Single Port, PROFINET Dual Port (optional via external connection module CDF600-2)
	Data transmission rate	10/100 MBit/s
EtherNet/IP™		✓
	Data transmission rate	10/100 MBit/s
EtherCAT®		√
	Type of fieldbus integration	Optional over external fieldbus module CDF600
Serial		√ , RS-232, RS-422, RS-485
	Function	Host, AUX
	Data transmission rate	2,400 Baud 115.2 kBaud, AUX: 57.6 kBaud (RS-232)
CAN		✓
6 ,		•
7 ,	Function	SICK CAN sensor network CSN (master/slave, multiplexer/server)
	Function Data transmission rate	SICK CAN sensor network CSN (master/slave, multiplexer/server)
CANopen		SICK CAN sensor network CSN (master/slave, multiplexer/server)
		SICK CAN sensor network CSN (master/slave, multiplexer/server) 20 kbit/s 1 Mbit/s
	Data transmission rate	SICK CAN sensor network CSN (master/slave, multiplexer/server) 20 kbit/s 1 Mbit/s
CANopen	Data transmission rate Data transmission rate	SICK CAN sensor network CSN (master/slave, multiplexer/server) 20 kbit/s 1 Mbit/s 20 kbit/s 1 Mbit/s
CANopen	Data transmission rate Data transmission rate	SICK CAN sensor network CSN (master/slave, multiplexer/server) 20 kbit/s 1 Mbit/s 20 kbit/s 1 Mbit/s
CANopen PROFIBUS DP	Data transmission rate Data transmission rate	SICK CAN sensor network CSN (master/slave, multiplexer/server) 20 kbit/s 1 Mbit/s 20 kbit/s 1 Mbit/s Optional over external fieldbus module CDF600-2
CANopen PROFIBUS DP	Data transmission rate Data transmission rate Type of fieldbus integration	SICK CAN sensor network CSN (master/slave, multiplexer/server) 20 kbit/s 1 Mbit/s 20 kbit/s 1 Mbit/s Optional over external fieldbus module CDF600-2
CANopen PROFIBUS DP DeviceNet™	Data transmission rate Data transmission rate Type of fieldbus integration	SICK CAN sensor network CSN (master/slave, multiplexer/server) 20 kbit/s 1 Mbit/s 20 kbit/s 1 Mbit/s Optional over external fieldbus module CDF600-2 Optional, over external connection module CDM + CMF
CANopen PROFIBUS DP DeviceNet™ Digital inputs	Data transmission rate Data transmission rate Type of fieldbus integration	SICK CAN sensor network CSN (master/slave, multiplexer/server) 20 kbit/s 1 Mbit/s 20 kbit/s 1 Mbit/s 4 Optional over external fieldbus module CDF600-2 4 Optional, over external connection module CDM + CMF 3 ("Sensor 1", 2 inputs via optional parameter storage CMC600 in CDB620/CDM420)
CANopen PROFIBUS DP DeviceNet™ Digital inputs Digital outputs	Data transmission rate Data transmission rate Type of fieldbus integration	SICK CAN sensor network CSN (master/slave, multiplexer/server) 20 kbit/s 1 Mbit/s 20 kbit/s 1 Mbit/s 4 Optional over external fieldbus module CDF600-2 4 Optional, over external connection module CDM + CMF 3 ("Sensor 1", 2 inputs via optional parameter storage CMC600 in CDB620/CDM420) 2 (Via optional CMC600 parameter memory in CDB620/CDM420)
CANopen PROFIBUS DP DeviceNet™ Digital inputs Digital outputs Reading pulse	Data transmission rate Data transmission rate Type of fieldbus integration Type of fieldbus integration	SICK CAN sensor network CSN (master/slave, multiplexer/server) 20 kbit/s 1 Mbit/s 20 kbit/s 1 Mbit/s Optional over external fieldbus module CDF600-2 Optional, over external connection module CDM + CMF 3 ("Sensor 1", 2 inputs via optional parameter storage CMC600 in CDB620/CDM420) 2 (Via optional CMC600 parameter memory in CDB620/CDM420) Digital inputs, non-powered, serial interface, auto pulse, CAN

CLV622-1120 | CLV62x

BAR CODE SCANNERS

Configuration software SOPAS ET

Ambient data


Electromagnetic compatibility (EMC)	EN 61000-6-3 (2001-10) / EN 61000-6-2:2005
Vibration resistance	EN 60068-2-6 (1995)
Shock resistance	EN 60068-2-27 (1993)
Ambient operating temperature	0 °C +40 °C
Storage temperature	-20 °C +70 °C
Permissible relative humidity	90 %, Non-condensing
Ambient light immunity	2,000 lx, on bar code
Bar code print contrast (PCS)	≥ 60 %

Classifications

ECI@ss 5.0	27280102
ECI@ss 5.1.4	27280102
ECI@ss 6.0	27280102
ECI@ss 6.2	27280102
ECI@ss 7.0	27280102
ECI@ss 8.0	27280102
ECI@ss 8.1	27280102
ECI@ss 9.0	27280102
ETIM 5.0	EC002550
ETIM 6.0	EC002550
UNSPSC 16.0901	43211701


Dimensional drawing (Dimensions in mm (inch))

CLV62x Ethernet, front



Reading field diagram

Reading field height in mm (inch)



For devices with plastic reading window, the depth of field is reduced by approx. 10 %.





Recommended accessories

Other models and accessories → www.sick.com/CLV62x

	Brief description	Туре	Part no.
Mounting brackets and plates			
	Bracket with adapter board	Mounting bracket	2042902
Modules and	gateways		
NAME OF THE PARTY	External parameter memory for integration in CDB620/CDB650/CDM42x	CMC600-101	1042259
Plug connecto	ors and cables		
	Head A: female connector, M12, 12-pin, straight Head B: male connector, D-Sub-HD, 15-pin, straight Cable: Power, serial, CAN, digital I/Os, shielded, 2 m	YF2Z1B- 020XXXMHDAC	2041834
	Head A: male connector, M12, 4-pin, straight, D-coded Head B: male connector, RJ45, 8-pin, straight Cable: Ethernet, twisted pair, PUR, halogen-free, shielded, 2 m	YM2D24- 020EA1MRJA4	6034414
Modules			
	Small connection module for one sensor, 4 cable glands, base for CMC600	CDB620-001	1042256

Recommended services

Additional services → www.sick.com/CLV62x

	Туре	Part no.
Warranty extensions		
 Product area: Identification solutions, Vision, Distance sensors, Detection and ranging solutions Range of services: The services correspond to the scope of the statutory manufacturer warranty (SICK general terms and conditions of purchase), Long-term protection for calculable lump sum. Duration: Five-year warranty from date of purchase. 	Five-year extended warranty	1680671
Performance check		
 Product area: Bar code scanners Range of services: Inspection of defined functions, e.g., reading performance Documentation: Documentation of reading performance, Creation of a performance check log Duration: Additional work will be invoiced separately based on time spent Note: The prices do not include expenses or costs for the travel time 	Performance check CLV4xx/CLV6xx	1682028

	Туре	Part no.
Maintenance		
 Product area: Bar code scanners Range of services: Inspection, analysis and restoring of defined functions, Inspection and adjustment of reading configuration, code configuration, data processing and network or interfaces Documentation: Documentation of operating hours and archiving of parameters in a SICK database, Documentation of reading performance, Creation of a maintenance log Duration: Additional work will be invoiced separately based on time spent Note: The prices do not include expenses or costs for the travel time 	Maintenance CLV4xx/CLV6xx	1611420
Training		
 Product family group: Bar code scanners Range of services: SICK offers training courses for numerous target groups ranging from basic to expert levels, the training format and location can be worked out in collaboration with SICK Note: A minimum and maximum number of participants is determined based on the training format, depending on the training format, content and location, a training course may take place over the course of one or more work days Duration: The fixed price includes the specific training services agreed upon with the customer, the fixed price includes the work time required for the training services, the required work time depends on the range of services, Additional work will be invoiced separately based on time spent Travel expenses: The prices include costs for the travel time and expensestravel costs, such as flight or hotel expenses, are not included 	Training for the CLV6 series	1612231
Commissioning		
 Product area: Bar code scanners Range of services: Inspection of connection, fine adjustment, optimization of parameters of SICK product as well as verification tests, Setup of previously defined functions of reading configuration, code configuration, data processing and network, interfaces or inputs and outputs Documentation: Archiving of product parameters in a SICK database, Documentation of reading performance, Creation of a commissioning log Duration: Additional work will be invoiced separately based on time spent Note: The prices do not include expenses or costs for the travel time 	Commissioning CLV61x CLV64x	1681925

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

